

840

MATERIAL SAFETY DATA SHEET
Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Date of Prep: 9/19/02

SECTION 1

SUNNYSIDE CORPORATION FOR INFORMATION: (847) 541-6700
225 CARPENTER AVENUE
WHEELING, ILLINOIS 60090 (847) 541-6700 - SUNNYSIDE CORPORATION
EMERGENCY TELEPHONE (800) 424-8300 - CHEM TREC

Product Class: Ketone Manufacturer's Code: 840
Trade Name: ACETONE NPCA HMIS: Health: 1
Flammability: 3
Reactivity: 0

Product Appearance and Odor: Clear, water-white liquid; typical, pungent odor.

SECTION 2 - HAZARDOUS INGREDIENTS

OCCUPATIONAL EXPOSURE LIMITS

INGREDIENT	CAS #	PERCENT	ACGIH TLV (TWA)	ACGIH TLV (STEL)	OSHA PEL (TWA)	OSHA PEL (STEL)	VAPOR PRESSURE
Acetone	67-64-1		500 PPM	750 PPM	750 PPM	1000 PPM	213 MM Hg @ 79° F

SECTION 3 - EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. If breathing is difficult, qualified medical personnel may administer oxygen and continue to monitor. Keep at rest. Get medical attention immediately.

EYE CONTACT: Flush eyes immediately with water for at least 15 minutes. Get prompt medical attention.

SKIN CONTACT: Flush with large amounts of water; use soap if available. Remove grossly contaminated clothing, including shoes, and launder before reuse. Get medical attention if skin irritation develops or persists.

INGESTION: If swallowed, do not induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 4 - PHYSICAL DATA

The following data represent approximate or typical values. They do not constitute product specifications.

Bolling Range:	133° (F) (I.B.P.)	Vapor Density:	Heavier than air
Evaporation Rate:	Slower than ether	% Volatile By Volume:	100%
Weight Per Gallon:	6.60 Lbs		
Solubility in Water:	Complete		

SECTION 5 - FIRE AND EXPLOSION DATA

Flammability Classification: Flammable Liquid - Class IB.

Flash Point: 0° (F) (Tag Closed Cup).

Autoignition Temperature: 869° (F)

Lower Explosive Limit: 2.5% @ 77° (F)

Extinguishing Media: Either allow fire to burn under controlled conditions or extinguish with alcohol resistant foam and dry chemical. Try to cover liquid spills with foam.

Unusual Fire and Explosion Hazards: Extremely flammable. Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations.

Special Fire Fighting Procedures: Use water spray to cool fire exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors.

Trade Name: ACETONE

Page 2 of 3

SECTION 6 – HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE:	500 PPM (ACGIH-Time weighted average).
EFFECTS OF OVEREXPOSURE	
Inhalation:	Vapors or mist may cause irritation of the nose and throat. Inhalation may cause dizziness, drowsiness, loss of coordination, disorientation, headache, nausea, and vomiting. In poorly ventilated areas or confined spaces, unconsciousness and asphyxiation may result.
Skin Contact:	Prolonged or repeated skin contact may cause irritation, discomfort and dermatitis.
Eye Contact:	Severely irritating and may injure cornea if not removed promptly. High vapor concentrations are also irritating.
Ingestion:	Product may be harmful or fatal if swallowed. Material is a pulmonary aspiration hazard. Material can enter lungs and cause damage. Ingestion of this product may cause central nervous system effects, which may include dizziness, loss of balance and coordination, unconsciousness, coma and even death.
Cardiogenicity:	Acetone is not listed by the NTP, IARC, or OSHA.

SECTION 7 – REACTIVITY DATA

Stability:	Stable
Conditions to Avoid:	Heat, sparks and flame.
Incompatibility (Materials to Avoid):	Caustics, amines, alkylamines, aldehydes, ammonia, strong oxidizing agents, and chlorinated compounds.
Hazardous Decomposition Products:	Thermal decomposition may yield carbon monoxide, carbon dioxide, aldehydes and ketones.
Hazardous Polymerization:	Will not occur.

SECTION 8 – SPILL OR LEAK PROCEDURES

Steps to be taken in case material is spilled or released: Remove ignition sources, evacuate area, avoid breathing vapors or contact with liquid. Recover free liquid or stop leak if possible. Dike large spills and use absorbent material for small spills. Keep spilled material out of sewers, ditches and bodies of water. Warn occupants and shipping in surrounding and downwind areas of fire and explosion hazard and request all to stay clear.

Waste disposal method: Incinerate under safe conditions; dispose of in accordance with local, state and federal regulations.

SECTION 9 – SAFE HANDLING AND USE INFORMATION

Respiratory Protection:	Where concentrations in air may exceed occupational exposure limits, NIOSH/MSHA approved respirators may be necessary to prevent overexposure by inhalation.
Ventilation:	Exposure levels should be maintained below applicable exposure limits - see Section 2. This product should not be used in confined spaces, or in a manner that will allow accumulation of high vapor concentrations. However, for controlled industrial uses when this product is used in confined spaces, heated above ambient temperatures or agitated, the use of explosion proof ventilation equipment is necessary.
Protective Gloves:	Chemical resistant gloves (Neoprene or Natural Rubber).
Eye Protection:	Chemical safety goggles and a face shield.
Other Protective Equipment:	Impervious clothing or boots where needed, eyewash facility and a safety shower.

SECTION 10 – SPECIAL PRECAUTIONS

Dept. of Labor Storage Category:	Flammable Liquid-Class IB.
Hygienic Practices:	Keep away from heat, sparks and flame. Keep containers closed when not in use. Avoid eye contact. Avoid prolonged or repeated contact with skin. Wash skin with soap and water after contact.
Additional Precautions:	Ground containers when transferring liquid to prevent static accumulation and discharge. Additional information regarding safe handling of products with static accumulation potential can be ordered by contacting the American Petroleum Institute (API) for API Recommended Practice 2003, entitled "Protection Against Ignitions Arising Out of Static, Lighting, and Stray Currents" (American Petroleum Institute, 1720 L Street Northwest, Washington, DC 20005), or the National Fire Protection Association (NFPA) for NFPA 77 entitled "Static Electricity" (National Fire Protection Association, 1 Batterymarch Park, P.O. Box 9101, Quincy, MA 02269-9101).
Empty Container Warning:	"Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition. They may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged and promptly returned to supplier or disposed of in an environmentally safe manner and in accordance with governmental regulations.

Trade Name: ACETONE Page 3 of 3

SECTION 11 -- ADDITIONAL INFORMATION

This product contains the following toxic chemical(s) which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

TOXIC CHEMICAL	CAS#	APPROXIMATE % BY WEIGHT
NONE	NONE	NONE

SARA Title III Hazard Categories: Immediate (Acute) Health, Delayed (Chronic) Health, Fire

Common Names: 2-Propanone, Dimethylketone

California Proposition 65: This product contains trace amounts of Benzene, a chemical known to the State of California to cause cancer, and Toluene, a chemical known to the State of California to cause birth defects or other reproductive harm.

TRANSPORTATION (U.S. D.O.T. land transportation in packages of 119 gallons or less)

- U.S. D.O.T. Proper Shipping Name: Acetone
- U.S. D.O.T. Hazard Class & Packing Group: Flammable Liquid, II
- U.S. D.O.T. LD. Number: UN 1090
- U.S. D.O.T. Hazardous Substance: Acetone RQ 5000 lbs.

Refer to 49 CFR for additional information. Exceptions or exemptions may exist for smaller quantities.

received 4/20/07 (10)

FAK-